

TABLE OF CONTENTS ~ BRIDGE SUPERSTRUCTURE DESIGN

Formatted: Font: 12 pt, Bold

5	Bridge Superstructure Design
5.1	General
5.1.1	Policy overview
5.1.2	Design information
5.1.3	Definitions
5.1.4	Abbreviations and notation
5.1.5	References

5 Bridge Superstructure Design**5.1 General**

The series of articles under Section 5, Bridge Superstructure Design, is intended to fit together as a unit. As much as possible, cross references are used to avoid duplication.

5.1.1 Policy overview

In the Office of Bridges and Structures, the design of typical highway bridges proceeds from preliminary to final design sections. The preliminary design section selects the superstructure type based on bridge site information, available locations for substructure components, spans between substructure components, and criteria stated in *Bridge Design Manual* Section 3, Preliminary Design ~~(in process)~~. In some cases the preliminary design section also considers aesthetic criteria in Section 4, Aesthetic Design (in process). A final design section then completes the structural design and detailing following the policies in Section 5, Bridge Superstructure Design, and Section 6, Bridge Substructure Design.

In the past the office followed AASHTO Standard Specifications but now has transitioned to AASHTO LRFD Specifications for superstructure design. With the transition the superstructure sections of the manual based on the AASHTO Standard Specifications have been withdrawn and archived.

The office interprets the basic AASHTO LRFD Specifications when designing superstructures, bearings, and additional components and specifies rules for detailing these components. This series of articles on superstructure components covers most typical designs but does not cover special bridge designs for signature bridges and long-span bridges.

In all cases, superstructure components need to be designed for vertical and lateral loads, strength, serviceability, and economy considering the entire bridge structure.

For typical highway bridge superstructures, the office generally selects among four types: continuous concrete slab (CCS), pretensioned prestressed concrete beam (PPCB), continuous welded plate girder (CWPG), and rolled steel beam (RSB). In general CCS bridges are used for short spans up to 59 feet (17.983 m) and lengths to 150 feet (45.720 m) or where minimum superstructure depth is required over short spans. PPCB bridges are used for longer spans to 155 feet (47.244 m). CWPG bridges are used for spans longer than 155 feet (47.244 m), where minimum superstructure depth is required, or where the horizontal alignment is sharply curved. Standard three-span RSB bridges have center spans to 136 feet (41.450 m) and will be available in 2010 after they have been redesigned to the AASHTO LRFD Specifications are used for spans to 120 feet (36.576 m) on sites where the predesigned structures are appropriate. Except for unusual conditions the office limits bridge skew to 45 degrees.

Standard sheets and details and signed standard bridge plans that follow current policies are available for efficient design of the typical superstructures. In all cases, however, the standard sheets and standard bridge plans need to be supplemented with additional sheets to produce a complete plan set for a bridge project.

The office has signed standard plans for ~~a four~~ series of three-span CCS bridges, ~~a series of two-span PPCB bridges~~, a series of three-span PPCB bridges ~~(to be fully available in 2010)~~, and a series of three-span RSB bridges ~~(to be available in 2010)~~ that may be used for relatively simple alignments and site conditions. The standard CCS bridges, which are intended for stream and small valley crossings, have four roadway widths from 24 to 44 feet (7.315 to 13.411 m), lengths varying from 70 to 150 feet (21.336 to 45.720 m), and skews from 0 to 45 degrees. ~~The standard two-span PPCB bridges, which are intended primarily for grade separations, have lengths varying from 220 to 260 feet (67.060 to 79.250 m) and skews from 0 to 15 degrees.~~ The standard three-span PPCB bridges have lengths varying from 126.33 to 243 feet (38.505 to 74.066 m) and skews from 0 to 45 degrees. The standard rolled steel beam bridges, which are intended for stream crossings and county road overpasses, have lengths varying from 160 to ~~340~~399 feet (48.770 to ~~103.630~~91.440 m), span ratios of 0.75-1.00-0.75, and skews from 0 to ~~45~~30 degrees.

The general availability of standard sheets and standard bridge plans ~~for primary highway system projects~~ is summarized in Table 5.1.1. All items listed in the table have roadway widths of at least 30 feet (9.144 m).

Table 5.1.1. Summary of standard sheets and signed standard bridge plan availability

Superstructure type	Number of spans	AASHTO live load and specification	
		Standard sheets	Signed standard plan sets
CCS, J30, J40, and J44 series ⁽¹⁾	3	---	HL-93 LRFD superstructure , HS-25 standard substructure ⁽³⁾
PPCB	---	HL-93 LRFD	---
PPCB, BT two-span series	2	---	HS-20 standard, except HL-93 LRFD beams
PPCB, HSI single span series	1	---	Withdrawn, but will be reissued for HL-93 LRFD
PPCB, H30, H40, and H44 series ⁽¹⁾	3	---	HL-93 LRFD ⁽³⁾ superstructure , HS-25 standard substructure ⁽³⁾
CWPG	---	HL-93 LRFD	---
RSB, rolled beam series	3	---	HL-93 LRFD ⁽⁴⁾ HS-20 standard

Table notes:

(1) The 24-foot (7.315-m) wide ~~bridges (not shown in the table) are~~J-series of bridges, J24, is intended only for county and city use.

(2) The standard sheets available for three-span CCS structures designed under the AASHTO Standard Specifications have been voided.

(2)(3) ~~The H30 bridge standards will be available in 2010.~~

(3)(4) ~~The redesigned RSB series will be available in 2010. HS-25 standard substructure is intended to be approximately equivalent to a HL-93 LRFD substructure.~~

The office prefers jointless bridges and therefore, wherever practical, selects integral abutments and continuous construction at piers. In cases where expansion joints are necessary due to bridge length, the expansion joints are to be designed according to the guidelines in a subsequent article [BDM 5.8.3, in process].

5.1.2 Design information

Reserved

Formatted: Superscript

Formatted: Superscript

Formatted: Superscript

5.1.3 Definitions

Reserved

5.1.4 Abbreviations and notation

CCS, continuous concrete slab

CWPG, continuous welded plate girder

PPCB, pretensioned prestressed concrete beam

RSB, rolled steel beam

5.1.5 References

Reserved